

● PROFESSIONAL LED INDICATORS Ø8.1mm Mounting

FEATURES



677 SERIES








PACK QUANTITY = 10 PIECES

- Black anodised aluminium housing
- Sealed to IP67
- Wide viewing angle
- Suitable for high vibration applications
- Internal reverse protection diode fitted as standard in all voltage models.
- Smoked lens for good on/off contrast ratio

SPECIFICATION

Ordering Information & Typical Technical Characteristics (Ta = 25°C)

Mean Time Between Failure = 100,000 Hours. Luminous intensity figures refer to the unmodified discrete LED.


PART NUMBER	COLOUR	LENS	VOLTAGE DC (Vdc) Vopr	CURRENT DC (mA) Iopr	LUMINOUS INTENSITY Iv@20mA (mcd)	WAVE LENGTH λp (nm)	OPERATING TEMP Topr	STORAGE TEMP Tstg	
HIGH INTENSITY									
01-677-501-21	Red	 Smoked	12	20	11000	643	-40 ~ +95 [^]	-40 ~ +100	Yes
01-677-521-21	Yellow	 Smoked	12	20	16000	591	-40 ~ +95 [^]	-40 ~ +100	Yes
01-677-532-21	Green	 Smoked	12	20	23000	527	-40 ~ +95 [^]	-40 ~ +100	Yes
01-677-930-21	Blue	 Smoked	12	20	7000	470	-40 ~ +95 [^]	-40 ~ +100	Yes
01-677-501-23	Red	 Smoked	24-28	20	11000	643	-40 ~ +95 [^]	-40 ~ +100	Yes
01-677-521-23	Yellow	 Smoked	24-28	20	16000	591	-40 ~ +95 [^]	-40 ~ +100	Yes
01-677-532-23	Green	 Smoked	24-28	20	23000	527	-40 ~ +95 [^]	-40 ~ +100	Yes
UNITS			Vdc	mA	mcd	nm	°C	°C	



Other voltages AC/DC available. Please contact our Technical Sales.

[^] = Products must be derated according to the derating information (page 3). Each derating graph refers to specific LEDs.

677 Series




Dimensions in mm (Typical)
Not to scale

Anode termination indicated by red sleeve
Mounting hole to be clean and burr free

MATERIALS

Body	Black Anodised Aluminium
Nut	Bright Nickel Plated Brass
Panel Seal	Viton
Termination Tags	Silver Flash Coated Brass
Fresnel lens	Polycarbonate
Encapsulation	PC5430 Resin
Lock Washer	Spring Steel

PUSH-ON CONNECTORS



925-000-00 is brass tin plated.
For use with 677 series lamps.

Dimensions in mm (Typical)
Not to scale

TECHNICAL CHARACTERISTICS



SERIES	MAXIMUM POWER DISSIPATION	MAXIMUM REVERSE VOLTAGE	PANEL CUTOUT	NUT MOUNTING TORQUE	MINIMUM MOUNTING CENTRES	MIN/MAX. PANEL THICKNESS
677	700	3* / 1000•	8.1	0.6	x,y = 14.5	1.5-13.0
UNITS	mW	Vdc	mm	Nm	mm	mm

* = Current Version • = Voltage Version

OPTIONAL FLYING LEAD TERMINATIONS

ORDER CODE SUFFIX	SUPPLY VOLTAGE	WIRE COLOUR	WIRE LENGTH	NO/DIAMETER OF CONDUCTORS	DIAMETER OVER INSULATION	COMMENTS
15	DC Products	Red-anode / Black-cathode	150mm	19/0.15mm	1.2mm	Customised lengths available
15	AC Products	Brown-live / Blue-neutral	150mm			
19	DC Products	Red-anode / Black-cathode	1000mm			
19	AC Products	Brown-live / Blue-neutral	1000mm			

DERATING INFORMATION



ALSO AVAILABLE

Part numbers also available in the 677 Series:

PART NO.	COLOUR	VOLTAGE DC (Vdc) Vopr
01-677-501-22-R	Red	24Vdc
01-677-521-22	Yellow	24Vdc
01-677-532-22	Green	24Vdc
01-677-930-22	Blue	24Vdc
UNITS		

The products listed above illustrate all of the options available to order. These products may have custom modifications that alter their operation beyond the generic information contained within this datasheet.