


# Orion

## Indoor Linear LED Light system

The Orion is a highly reliable, professional system utilising LED technology to provide a strip or wash of high intensity light that can be used in a variety of applications.

Orion Linear Light System is manufactured utilising high intensity LEDs encased in a durable aluminium extrusion with a frosted acrylic lens.




# Orion



## Part Number Sequencing


### Single Colour Part Number Sequencing

PART NUMBER	COLOUR	TOTAL ILLUMINATED LENGTH (mm) (DIMENSION x)	TOTAL UNIT LENGTH (mm) (DIMENSION y)	TYPICAL POWER CONSUMPTION (Watts)	TYPICAL CURRENT (mA)	POWER SUPPLY	
<b>Single Colour Units</b>							
LSX 0339 WH 1000	Cool white	300	339	3.0	125	PSU***24V/1A XLR	Yes
LSX 0639 WH 1000	Cool white	600	639	6.0	250	PSU***24V/1A XLR	Yes
LSX 0939 WH 1000	Cool white	900	939	9.0	375	PSU***24V/1A XLR	Yes
LSX 1239 WH 1000	Cool white	1200	1239	12.0	500	PSU***24V/1A XLR	Yes
LSX 1539 WH 1000	Cool white	1500	1539	15.0	625	PSU***24V/1A XLR	Yes
LSX 1839 WH 1000	Cool white	1800	1839	18.0	750	PSU***24V/1A XLR	Yes
LSX 2139 WH 1000	Cool white	2100	2139	21.0	875	PSU***24V/1A XLR	Yes
LSX 2439 WH 1000	Cool white	2400	2439	24.0	1000	PSU***24V/3A XLR	Yes

Please note these units are also available in the following colours:

Red, Yellow, Green and Blue. Please contact our sales department for further details.

### Colour Changing Part Number Sequencing

PART NUMBER	COLOUR	TOTAL ILLUMINATED LENGTH (mm) (DIMENSION x)	TOTAL UNIT LENGTH (mm) (DIMENSION y)	TYPICAL POWER CONSUMPTION (Watts)	TYPICAL CURRENT (mA)	POWER SUPPLY	
<b>Colour Changing Units</b>							
LSX 0439 CC 1000	Colour Changing	400	439	6.7	280	PSU***24V/1A JP	Yes
LSX 0639 CC 1000	Colour Changing	600	639	10.1	420	PSU***24V/1A JP	Yes
LSX 0839 CC 1000	Colour Changing	800	839	13.4	560	PSU***24V/1A JP	Yes
LSX 1039 CC 1000	Colour Changing	1000	1039	16.8	700	PSU***24V/1A JP	Yes
LSX 1239 CC 1000	Colour Changing	1200	1239	20.2	840	PSU***24V/1A JP	Yes
LSX 1439 CC 1000	Colour Changing	1400	1439	23.5	980	PSU***24V/1A JP	Yes
LSX 1639 CC 1000	Colour Changing	1600	1639	26.9	1120	PSU***24V/3A JP	Yes
LSX 1839 CC 1000	Colour Changing	1800	1839	30.2	1260	PSU***24V/3A JP	Yes
LSX 2039 CC 1000	Colour Changing	2000	2039	33.6	1400	PSU***24V/3A JP	Yes

- When ordering please replace \*\*\* in the power supply code with the correct connection for your geographical location.  
GBR = for use in Great Britain USA = for use in North America EUR = for use in Europe
- Colour Changing Orion units will require a Colour Changing Control Unit (Part No. CCBOXHD) to provide a 30 second colour roll, together with a relevant power supply.

# Orion

## Technical Specifications

Ta = 25 °C

Supply Voltage:	24Vdc.
Typical Current:	As Specified.
Ambient Light conditions:	Zero to Daylight.
LED Spacing:	10mm for Single Colour 6.6mm for Colour Changing
Storage Temperature:	-20°C to + 50 °C.
Operating Temperature:	-20°C to + 50 °C.

### MATERIALS

Extruded Housing:	Aluminium.
Optical Lens:	Acrylic D6 frosted grade.
LED Lens:	Diffused Epoxy.
End Caps:	Aluminium.
Finish:	All aluminium natural anodised to AA25.

Stand alone single colour units will require a power supply as recommended in the product data overleaf. Multiple units can be interlinked, please contact our sales department for further details.

Colour Changing Orion units will require a Colour Changing Control Unit (Part No. CCBOXHD) to provide a 30 second colour roll, together with a relevant power supply.

These units may also be driven by more sophisticated controllers incorporating DMX protocol for integration with existing lighting systems.

- Contact Sales for more details.




## Features & Benefits


- RoHS Compliant
- Virtually maintenance free
- Ultra low power consumption
- Impact resistant
- Ease of Installation
- Unlimited colour options utilising RGB technology

## Applications


- Indoor lighting
- Corridor and stairway lighting
- Feature lighting
- Emergency lighting
- Retail display lighting
- Covers
- Exhibition and display applications




Side View  
End Cap



Cushion Clip  
Front View



Cushion Clip  
Side View



All measurements are in mm

### How to Order:

website: [www.marl.co.uk](http://www.marl.co.uk) • email: [sales@marl.co.uk](mailto:sales@marl.co.uk) • webstore: [www.leds.co.uk](http://www.leds.co.uk)

Marl International Limited • Marl Business Park • Ulverston • Cumbria LA12 9BN • United Kingdom

Tel: +44 (0)1229 582430 • Fax: +44 (0)1229 585155

The information contained in this datasheet does not constitute part of any order or contract and should not be regarded as a representation relating to either products or service. Marl International reserve the right to alter without notice the specification or any conditions of supply for products or service.



BS EN ISO 9001:2000  
Approved Manufacturer