


### PRODUCT:

HIGH CRI LED FLEX STRIP Hybrid Color  
Temperature 2835 12V



### FEATURES:

10 mm width flexible PCB with adhesive backing  
5-meter length per roll  
95 CRI, 2700K / 3200K / 5600K / 6500K  
15 W / meter (4.6 W / foot)  
12V constant voltage compatible  
Cutttable every 6 LEDs (50 mm)



### DESCRIPTION

High CRI LED flexible strips are extremely versatile and can be installed in a variety of linear and curved surfaces alike. Enhanced copper traces with precision SMT resistors provide consistently high power and brightness. 3M® adhesive backing allows for quick installation.


### ELECTRICAL-OPTICAL CHARACTERISTICS (T<sub>A</sub> = 25 °C)

PARAMETER	SYMBOL	VALUE			UNIT	TOLERANCE	CONDITION
		MIN.	TYP.	MAX.			
Power per meter*	--	--	15	18	W	--	V <sub>f</sub> = 12V
Forward current per meter	I <sub>f</sub>	--	1.25	1.5	A	--	V <sub>f</sub> = 12V
Luminous flux per meter	Φ <sub>2700K</sub>	--	450	--	lm	--	V <sub>f</sub> = 12V
	Φ <sub>3200K</sub>	--	450	--			
	Φ <sub>5600K</sub>	--	650	--			
	Φ <sub>6500K</sub>	--	650	--			
Correlated color temperature	CCT <sub>2700K</sub>	2625±75		2775±75	K	--	V <sub>f</sub> = 12V
	CCT <sub>3200K</sub>	3125±75		3275±75			
	CCT <sub>5600K</sub>	5450±150		5750±150			
	CCT <sub>6500K</sub>	6250±250		6750±250			
Color rendering index	R <sub>a</sub>	95	--	--	--	--	V <sub>f</sub> = 12V
TCS R9 (CRI Red)	R <sub>9</sub>	--	90	--	--	--	V <sub>f</sub> = 12V
Chromaticity coordinates	(X,Y)	--	--	--	--	±0.005	--
Viewing angle	2θ <sub>1/2</sub>	--	120	--	Deg	±5	V <sub>f</sub> = 12V

\*Unless otherwise noted, specifications are based on a 1 meter segment. Due to electrical resistance, power draw per meter decreases approximately by 0.05A for each additional meter increase per segment.


ORDERING INFORMATION		
PART NUMBER	CCT	CHROMATICITY BINS
YJ-BC-HRB-2835L-12V-G02-2765	2700K ± 150K	27L, 27R
	6500K ± 500K	65L, 65R
YJ-BC-HRB-2835L-12V-G02-3256	3200K ± 150K	32L, 32R
	5600K ± 300K	56L, 56R
YJ-BC-HRB-2835L-12V-G02-XXXX	CUSTOM	

ABSOLUTE MAXIMUM RATING (T <sub>A</sub> = 25 °C)			
PARAMETER	SYMBOL	LIMIT	UNIT
Power Consumption	P <sub>D</sub>	18	W/m
Operating Temperature	T <sub>opr</sub>	-40 ~ +85	°C
Storage Temperature	T <sub>stg</sub>	-30 ~ +85	°C






CHROMATICITY BINS & COORDINATES									
CCT	BIN	CIE 1931 COORDINATES							
		X0	Y0	X1	Y1	X2	Y2	X3	Y3
6500K	65L	0.3067	0.3235	0.3088	0.3121	0.3143	0.3178	0.3128	0.3295
	65R	0.3128	0.3295	0.3143	0.3178	0.3205	0.3241	0.3192	0.3359
5600K	56L	0.3237	0.3401	0.3243	0.3269	0.3303	0.3320	0.3300	0.3460
	56R	0.3300	0.3460	0.3303	0.3320	0.3370	0.3378	0.3372	0.3526
3200K	32L	0.4194	0.4042	0.4130	0.3882	0.4201	0.3909	0.4269	0.4069
	32R	0.4269	0.4069	0.4201	0.3909	0.4275	0.3935	0.4347	0.4095
2700K	27L	0.4542	0.4166	0.4459	0.4005	0.4552	0.4025	0.4642	0.4185
	27R	0.4642	0.4185	0.4552	0.4025	0.4652	0.4043	0.4749	0.4203



**TYPICAL SPECTRAL DISTRIBUTION GRAPHS**





#### ADDITIONAL NOTES

##### SELECTING A POWER SUPPLY

*The wattage/ampere requirement is directly proportional to the length of LED flexible strip installed. Calculate the power requirement by multiplying the total length in meters by the maximum wattage or ampere per meter. For additional power supply stability, we recommend specifying 25% additional power capacity above the requirement. For example, a 5 meter length would require 5 meters x 18 W / meter = 90W; for power supply stability, we would recommend a power supply that is capable of supplying at least W (60W + 25% x 60W).*

##### DIMMING

*Our LED flex strips are compatible with 1-10V and PWM dimming systems.*

##### HEAT MANAGEMENT

*Heatsinking is not necessary if product is used in standard indoor environments where ambient temperatures do not exceed 50°C. Our testing at  $T_a = 25^\circ\text{C}$  shows LED solder point temperatures stabilizing at 68°C. Maximum allowed LED solder point temperature is 105°C.*